

● 完善的保护系统

整机具有全功能保护。它包括，电源软启动、直流过载短路、过热、超高频、削波限幅等功能，特别无继电器输出保护，它具有反应迅速、准确，是继电器无法相比的。

● Perfect protection system

It has full function protection. It includes power soft start, overload and short circuit, DC, overheating, UHF, clipping limiter function, especially without output relay protection, it has reflected the rapid, accurate, is the relay can not be compared.

● 输入输出连接器

为了提高本机工作的可靠性，所有输入输出全部采用进口正版的Neutrik，全系列采用安森美（原摩托罗拉）功率输出金封管。

● Input and output connectors

In order to improve the reliability of the machine work, all the input and output of all imported genuine Neutrik, using the full range of Semiconductor (formerly Motorola) Gold sealed tube output.

● 优良的散热系统

采用高效率短程风道的双层铜质带状散热片，使输出晶体管保存在同等的温度，其散热性能是数倍于铝质散热器。

● Excellent heat dissipation system

High efficiency double short duct fins copper strip, maintaining the output transistor in the same temperature, the cooling performance is several times the aluminum radiator.

14000W



Mult-Control





技术参数 SPECIFICATION

型号 Model	HD-2.08	HD-2.13	HD-2.15	HD-2.18	HD-2.24	HD-4.13	HD-4.15
8欧姆: 8 ohm Stereo Power:	2x800W	2x1300W	2x1500W	2x1800W	2x2400W	4x1300W	4x1500W
4欧姆: 4 ohm Stereo Power:	2x1600W	2x2200W	2x2700W	2x3200W	2x4350W	4x2200W	4x2550W
2欧姆: 2 ohm Stereo Power:	2x2000W	2x3000W	2x4000W	2x4800W	2x7000W	4x2400W	4x3400W
桥接8欧姆: 8 ohm Bridged Monon Power:	1x3200W	1x4200W	1x5400W	1x6400W	1x8700W	2x4400W	2x4500W
桥接4欧姆: 4 ohm Bridged Monon Power:	1x4000W	1x6000W	1x8000W	1x9600W	1x14000W	2x4800W	2x6800W
尺寸(W x H x D): Size(W x H x D):	483x425x88mm			483x445x88mm			
重量: Weight(net):	14Kg	14.5Kg	14.5Kg	15Kg	15Kg	17Kg	17Kg

产品参数如有改动，恕不另行通知